

NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING

66" H x 60" W x 24" D 2 FRONT DOOR DESIGN



FILE NUMBER: E507642

- ENCLOSURE MATERIAL**
- ☐ POWDER COATED STEEL (CS)
- ☐ POWDER COATED ALUMINUM (AL)

- POWDERCOAT COLOR**
- ☐ STANDARD WHITE
- ☐ LIGHT GRAY ANSI 70
- ☐ DARK GRAY ANSI 61
- ☐ STANDARD BLACK
- ☐ CUSTOM _____

- BASE EXTENSION**
- ☐ 2" BASE EXTENSION
- ☐ 4" BASE EXTENSION
- ☐ 6" BASE EXTENSION
- ☐ 12" BASE EXTENSION
- ☐ NOT REQUIRED


- EXTERIOR MOUNTING**
- ☐ EXTERIOR MOUNTING BRACKETS (STANDARD)
- ☐ NOT REQUIRED

OPTIONAL

AIR
CONDITIONER
SEE (PAGE 5)

OPTIONAL

A/C HATCH
DOOR



FRONT VIEW

OPTIONAL

REMOVABLE
LIFTING PAD-EYES

WELDED
LIFTING PADS
(STANDARD)

OPTIONAL

FILTER FAN(S)
SEE (PAGE 6)

LIFTING EYE

- ☐ WELDED PADS (STANDARD)
- ☐ REMOVABLE PADEYES

DOOR HINGE

- ☐ PIANO HINGE (STANDARD)
- ☐ LIFT OFF HINGE

DOOR LATCH OPTIONS

- ☐ 3 PT. LATCH (STANDARD)
- ☐ CLAMP SCREW WITH HASP

DOOR HANDLE

- ☐ PADLOCK PROVISION (STANDARD)
- ☐ KEYLOCK (OPTION)

***WINDOW OPTIONS**

- ☐ TEMPERED GLASS
- ☐ NOT REQUIRED

*NOTE: UL & NON-UL OPTIONS
AVAILABLE

OPTIONAL

LIFT OFF HINGE

N4-666024-FSDDECXX (X1)

ALL DIMENSIONS ARE ESTIMATED IN INCHES
AND MAY VARY DUE TO SELECTED OPTIONS.

COMPANY NAME

APPROVED (PRINTED NAME)

SIGNATURE


DATE

NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING

66" H x 60" W x 24" D 2 FRONT DOOR DESIGN



FILE NUMBER: E507642



N4-666024-FSDDECXX (X1)

**NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING**

66" H x 60" W x 24" D
2 FRONT DOOR DESIGN



FILE NUMBER: E507642

BASE ACCESS COVER PLATE
(OPTION)


- ☐ 8x8 PLATE (6x6 CUT-OUT)
☐ 8x16 PLATE (6x14 CUT-OUT)
☐ 12x12 PLATE (10x10 CUT-OUT)
☐ 16x16 PLATE (14x14 CUT-OUT)
☐ CUSTOM SIZE _____
☐ NOT REQUIRED

ACCESS COVER PLATE MAT'L

- ☐ POWDER COATED STEEL
☐ POWDER COATED ALUMINUM
☐ STAINLESS STEEL, 304

CONDUIT/CABLE SEAL OPTIONS

- ☐ ROXTEC SEAL SOLUTION
☐ PIPE FITTING HUB
☐ CABLE GLAND




TOP CROSS SECTION VIEW B-B

66" H x 60" W x 24" D
2 FRONT DOOR DESIGN

NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING




FILE NUMBER: E507642



TOP VIEW

- DOOR STOPPER**
- ☐ INSTALL DOOR STOPPER
 - ☐ NOT REQUIRED



ENCLOSURE MOUNTING
BRACKET DETAILS

N4-666024-FSDDECXX (X1)

NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING

66" H x 60" W x 24" D 2 FRONT DOOR DESIGN



FILE NUMBER: E507642

A/C UNIT AND SERVICE HATCH DOOR (OPTION)

AIR CONDITIONER

- ☐ 1000 BTU
☐ 1500 BTU
☐ 2000 BTU
☐ 3000 BTU
☐ 4000 BTU
☐ 5000 BTU
☐ 6000 BTU
☐ 8000 BTU
☐ SPECIFY _____
☐ NOT REQUIRED

A/C VOLTAGE/ HZ

- ☐ 115 VOLTS
☐ 230 VOLTS
☐ 480 VOLTS
☐ 60 HZ
☐ 50 HZ
☐ 48 VDC (CS011 A/C ONLY)

A/C INTEGRATED HEATER


- ☐ 350 WATTS (CS011 A/C ONLY)
☐ 500 WATTS
☐ 1000 WATTS
☐ EXTERNAL HEATER

ADDITIONAL A/C OPTIONS

- ☐ CORROSION PROTECTION PACKAGE
☐ DRY CONTACT (OUTPUT SIGNAL)
☐ 2" DEEP FILTERS
☐ PROXIMITY SWITCH (ON/OFF)

AIR CONDITIONER- SCADA

- ☐ MODBUS RTU 485 (2 WIRE)
 REMOTE NETWORK
 ETHERNET CONNECTION
☐ MODBUS GATEWAY
 ADD-ON



LEFT SIDE

SUN REFLECTIVE SOLUTION

- ☐ TOP SUNSHIELD COVER

THERMAL SPECIFICATIONS

- ☐ OUTSIDE (AMBIENT) _____ °F
☐ INTERIOR TEMP. _____ °F
☐ HEAT LOAD (WATTS) _____
☐ SUN / SHADE _____

ENCLOSURE INSULATION

- ☐ 1/2 RADIANT BARRIER (STANDARD)
☐ 3/4 RADIANT BARRIER
☐ 1 RADIANT BARRIER
☐ NOT REQUIRED

A/C SERVICE DOOR

- ☐ INSTALL A/C SERVICE DOOR
☐ NOT REQUIRED

A/C SERVICE DOOR HINGE

- ☐ REMOVABLE HINGE
☐ CONTINUOUS HINGE

A/C ADAPTOR PLATE

- ☐ INSTALL A/C ADAPTOR PLATE
☐ NOT REQUIRED

N4-666024-FSDDECXX (X1)

66" H x 60" W x 24" D
2 FRONT DOOR DESIGN

NEMA 4/12 - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING



FILE NUMBER: E507642

FILTERED FAN
SYSTEM (OPTION)

THERMAL SPECIFICATIONS

- ☐ OUTSIDE (AMBIENT) _____ °F
- ☐ INTERIOR TEMP. _____ °F
- ☐ HEAT LOAD (WATTS) _____
- ☐ SUN / SHADE _____

FAN SYSTEM

- ☐ PUSH-PULL SYSTEM (STANDARD)
- ☐ PUSH SYSTEM
- ☐ PULL SYSTEM
- ☐ NOT REQUIRED

FAN SERIES

- ☐ 60FL SERIES, 18" H (40-92 CFM)
- ☐ 180FL SERIES, 24" H (177-179 CFM)
- ☐ 225FL SERIES, 24" H (350 CFM)

FAN MATERIALS

- ☐ BAKED POWDER STEEL
- ☐ STAINLESS STEEL

FAN VOLTAGE/ HZ

- ☐ 115/60 (STANDARD)
- ☐ 230/60
- ☐ 12 VDC
- ☐ 24 VDC
- ☐ 48 VDC
- ☐ SPECIFY _____

ACCESSORIES AND OPTIONS


- ☐ REPLACEMENT FILTER

SUN REFLECTIVE SOLUTION

- ☐ TOP SUNSHIELD COVER

ENCLOSURE INSULATION

- ☐ 1/2 RADIANT BARRIER (STANDARD)
- ☐ 3/4 RADIANT BARRIER
- ☐ 1 RADIANT BARRIER
- ☐ NOT REQUIRED



N4-666024-FSDDECXX (X1)