

42" H x 60" W x 30" D
2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING

STAINLESS STEEL



OPTIONAL FILE NUMBER: E507642

REMOVABLE
LIFTING PAD-EYES

WELDED
LIFTING PADS
(STANDARD)

OPTIONAL
FILTER FAN(S)
SEE (PAGE 6)

LIFTING EYE
☐ WELDED PADS (STANDARD)
☐ REMOVABLE PADEYES

DOOR HINGE
☐ PIANO HINGE (STANDARD)
☐ LIFT OFF HINGE

DOOR LATCH OPTIONS
☐ 3 PT. LATCH (STANDARD)
☐ CLAMP SCREW WITH HASP

DOOR HANDLE
☐ PADLOCK PROVISION
(STANDARD)
☐ KEY (OPTION)

*WINDOW OPTIONS
☐ TEMPERED GLASS
☐ NOT REQUIRED

*NOTE: UL & NON-UL OPTIONS
AVAILABLE

OPTIONAL
LIFT OFF HINGE

ENCLOSURE MATERIAL
☐ 304 STAINLESS STEEL (S4)
☐ 316 STAINLESS STEEL (S6)

OPTIONAL
AIR
CONDITIONER
SEE (PAGE 5)


CORROSION PROTECTION PACKAGE
☐ EXTERIOR PASSIVATION (STANDARD)
☐ INTERIOR/EXTERIOR PASSIVATION (OPTION)
☐ NOT REQUIRED (ON REQUEST ONLY)

POWDERCOAT COLOR
☐ STANDARD WHITE
☐ LIGHT GRAY ANSI 70
☐ DARK GRAY ANSI 61
☐ STANDARD BLACK
☐ CUSTOM _____

BASE EXTENSION
☐ 2" BASE EXTENSION
☐ 4" BASE EXTENSION
☐ 6" BASE EXTENSION
☐ 12" BASE EXTENSION
☐ NOT REQUIRED

EXTERIOR MOUNTING
☐ EXTERIOR MOUNTING
BRACKETS (STANDARD)
☐ NOT REQUIRED

OPTIONAL
A/C HATCH
DOOR



FRONT VIEW

ALL DIMENSIONS ARE ESTIMATED IN INCHES
AND MAY VARY DUE TO SELECTED OPTIONS.

COMPANY NAME _____

APPROVED (PRINTED NAME) _____

SIGNATURE _____ DATE _____


N4X426030-FSDDECXX (X1)

42" H x 60" W x 30" D
2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING



FILE NUMBER: E507642



N4X426030-FSDDECXX (X1)

42" H x 60" W x 30" D
2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING



FILE NUMBER: E507642

BASE ACCESS COVER PLATE
(OPTION)


- ☐ 8x8 PLATE (6x6 CUT-OUT)
- ☐ 8x16 PLATE (6x14 CUT-OUT)
- ☐ 12x12 PLATE (10x10 CUT-OUT)
- ☐ 16x16 PLATE (14x14 CUT-OUT)
- ☐ CUSTOM SIZE _____
- ☐ NOT REQUIRED

ACCESS COVER PLATE MAT'L

- ☐ POWDER COATED STEEL
- ☐ POWDER COATED ALUMINUM
- ☐ STAINLESS STEEL, 304

CONDUIT/CABLE SEAL OPTIONS

- ☐ ROXTEC SEAL SOLUTION
- ☐ PIPE FITTING HUB
- ☐ CABLE GLAND



TOP CROSS SECTION VIEW B-B


42" H x 60" W x 30" D
2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING




FILE NUMBER: E507642

DOOR STOPPER
☐ INSTALL DOOR STOPPER
☐ NOT REQUIRED



TOP VIEW



ENCLOSURE MOUNTING
BRACKET DETAILS

N4X426030-FSDDECXX (X1)

42" H x 60" W x 30" D 2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING

A/C UNIT AND SERVICE
HATCH DOOR (OPTION)



FILE NUMBER: E507642

A/C MATERIAL (EXTERIOR)

- ☐ 304 STAINLESS STEEL
☐ 316 STAINLESS STEEL
☐ OTHER _____

AIR CONDITIONER

- ☐ 1000 BTU
☐ 1500 BTU
☐ 2000 BTU
☐ 3000 BTU
☐ 4000 BTU
☐ 5000 BTU
☐ 6000 BTU
☐ 8000 BTU
☐ SPECIFY _____
☐ NOT REQUIRED

A/C VOLTAGE/ HZ

- ☐ 115 VOLTS
☐ 230 VOLTS
☐ 480 VOLTS
☐ 60 HZ
☐ 50 HZ
☐ 48 VDC (CS011 A/C ONLY)

A/C INTEGRATED HEATER


- ☐ 350 WATTS (CS011 A/C ONLY)
☐ 500 WATTS
☐ 1000 WATTS
☐ EXTERNAL HEATER

ADDITIONAL A/C OPTIONS

- ☐ CORROSION PROTECTION PACKAGE
☐ DRY CONTACT (OUTPUT SIGNAL)
☐ 2" DEEP FILTERS
☐ PROXIMITY SWITCH (ON/OFF)

AIR CONDITIONER- SCADA

- ☐ MODBUS RTU 485 (2 WIRE)
 REMOTE NETWORK
 ETHERNET CONNECTION
☐ MODBUS GATEWAY
 ADD-ON

LEFT SIDESUN REFLECTIVE SOLUTION

- ☐ TOP SUNSHIELD COVER

THERMAL SPECIFICATIONS

- ☐ OUTSIDE (AMBIENT) _____ °F
☐ INTERIOR TEMP. _____ °F
☐ HEAT LOAD (WATTS) _____
☐ SUN / SHADE _____

ENCLOSURE INSULATION

- ☐ 1/2 RADIANT BARRIER (STANDARD)
☐ 3/4 RADIANT BARRIER
☐ 1 RADIANT BARRIER
☐ NOT REQUIRED

A/C SERVICE DOOR

- ☐ INSTALL A/C SERVICE DOOR
☐ NOT REQUIRED

A/C SERVICE DOOR HINGE

- ☐ REMOVABLE HINGE
☐ CONTINUOUS HINGE

A/C ADAPTOR PLATE

- ☐ INSTALL A/C ADAPTOR PLATE
☐ NOT REQUIRED

N4X426030-FSDDECXX (X1)

42" H x 60" W x 30" D
2 FRONT DOOR DESIGN

NEMA 4X - ENCLOSURE
ELECTRICAL CABINET
DOUBLE WIDE FREE STANDING



FILE NUMBER: E507642

FILTERED FAN
SYSTEM (OPTION)

THERMAL SPECIFICATIONS

- ☐ OUTSIDE (AMBIENT) _____ °F
- ☐ INTERIOR TEMP. _____ °F
- ☐ HEAT LOAD (WATTS) _____
- ☐ SUN / SHADE _____

FAN SYSTEM

- ☐ PUSH-PULL SYSTEM (STANDARD)
- ☐ PUSH SYSTEM
- ☐ PULL SYSTEM
- ☐ NOT REQUIRED

FAN SERIES

- ☐ 60FL SERIES, 18" H (40-92 CFM)
- ☐ 180FL SERIES, 24" H (177-179 CFM)
- ☐ 225FL SERIES, 24" H (350 CFM)

FAN MATERIALS

- ☐ BAKED POWDER STEEL
- ☐ STAINLESS STEEL

FAN VOLTAGE/ HZ

- ☐ 115/60 (STANDARD)
- ☐ 230/60
- ☐ 12 VDC
- ☐ 24 VDC
- ☐ 48 VDC
- ☐ SPECIFY _____

ACCESSORIES AND OPTIONS


- ☐ REPLACEMENT FILTER

SUN REFLECTIVE SOLUTION

- ☐ TOP SUNSHIELD COVER

ENCLOSURE INSULATION

- ☐ 1/2 RADIANT BARRIER (STANDARD)
- ☐ 3/4 RADIANT BARRIER
- ☐ 1 RADIANT BARRIER
- ☐ NOT REQUIRED



N4X426030-FSDDECXX (X1)