Mobile - 19" Rackmount - NEMA 4/12 Enclosures - Air Conditioned

NEMACOTM

Excellent Electrical Enclosures



Nemaco Tel. 281-251-2433 NemacoTech.com

NEMA 4/12 Type - 19" Rackmount Performance Enclosures

- Nemaco offers NEMA 4/12 Type Enclosures for performance applications.
- NEMA 4/12 Total Dust, Snow & Complete Water Washdown Resistance.
- NEMA 4/12 Easy Access 3 Point Turn Latch Handle System. Keylock & Keys Included.
- •NEMA 4/12 Air Conditioned Cooling Unit with Smart Remote Control Options Available.
- Nemaco offers Easy Rolling Caster Wheels. Total Locking Front Caster Wheels.

Nemaco offers the following Great Enclosure Features.

- Easy Access to Equipment: Single Front Door & Back Door (Option)is Available
- Fantastic Powder Coat Finished ANSI 61 Gray. Other Cool Colors Available.
- Adjustable 19" Rack Rail System that Fits Most Electrical Equipment Applications.
- •19" Rack Rails: Powder Coated Steel (standard), Aluminum & 304SS (Options) Available.
- •19" Rack Rails: 3/8" Sq. Hole (standard), #10-32 Tapped (Option) for all materials.
- Radiant Foam Insulation Barrier R=3.2, 0.5" thk, (R=5, 3/4" thk Option Available)
- Super Fast Customization Services (for holes, cut-outs & cables) are Available.

Note: Powder Coated Steel (3/8" Sq Hole) is the Standard Rack Rail System.

Aluminum Rack Rails & other options can be added to the enclosures.

Enclosure Part Number	Enclosure Size H x W x D	EIA Rack Space	NEMA 4/12 Rated Air Conditioners * Standard Units, 120 Volts, 60 Hz (A/C units 230 & 480 volts, 50/60 Hz are available)				Mobile Wheel Kit** H x W	Est. Enclosure Wt (Lbs) without A/C
N4-242424-19RC	24 x 24 x 24	11U	1000 BTU NE010126-04 (30 lbs)	1500 BTU NE010126-04 (52 lbs)	1000 to 2000 BTU CS011126-04 (42 lbs)	2000 BTU CS020126-04 (42 lbs)	6" x 36" (Max Wt 650 lbs)	164.2
N4-242430-19RC	24 x 24 x 30	11U						180.3
N4-242436-19RC	24 x 24 x 36	11U						196.5
N4-302424-19RC	30 x 24 x 24	15U	1000 BTU NE010126-04 (30 lbs)	1500 BTU NE010126-04 (52 lbs)	2000 BTU NE020126-04 (94 lbs)	2000 BTU CS020126-04 (42 lbs)	6" x 36" (Max Wt 650 lbs)	181.1
N4-302430-19RC	30 x 24 x 30	15U						198.8
N4-302436-19RC	30 x 24 x 36	15U						216.6
N4-362424-19RC	36 x 24 x 24	18U	1000 BTU NE010126-04 (52 lbs)	2000 BTU NE020126-04 (94 lbs)	3000 BTU NE030126-04 (94 lbs)	4000 BTU NE040126-04 (94 lbs)	6" x 36" (Max Wt 650 lbs)	198.0
N4-362430-19RC	36 x 24 x 30	18U						217.3
N4-362436-19RC	36 x 24 x 36	18U						236.7
N4-422424-19RC	42 x 24 x 24	20U	1000 BTU NE010126-04 (52 lbs)	2000 BTU NE020126-04 (94 lbs)	3000 BTU NE030126-04 (94 lbs)	4000 BTU NE040126-04 (94 lbs)	6" x 36" (Max Wt 650 lbs)	216.9
N4-422430-19RC	42 x 24 x 30	20U						237.8
N4-422436-19RC	42 x 24 x 36	20U						258.8
N4-482424-19RC	48 x 24 x 24	25U	1000 BTU NE010126-04 (52 lbs)	2000 BTU NE020126-04 (94 lbs)	3000 BTU NE030126-04 (94 lbs)	5000 BTU NE050126-04 (121 lbs)	6" x 36" (Max Wt 650 lbs)	233.8
N4-482430-19RC	48 x 24 x 30	25U						256.3
N4-482436-19RC	48 x 24 x 36	25U						278.9
N4-602424-19RC	60 x 24 x 24	32U	3000 BTU NE030126-04 (94 lbs)	4000 BTU NE040126-04 (94 lbs)	5000 BTU NE050126-04 (121 lbs)	6000 BTU NE060126-04 (121 lbs)	6" x 36" (Max Wt 650 lbs)	269.6
N4-602430-19RC	60 x 24 x 30	32U						295.4
N4-602436-19RC	60 x 24 x 36	32U						321.1

Note: * Refer to A/C Manufacturer's technical specifications. ** Extra Duty Wheel Casters are Available.